



Make It Yours.

**GXII GOLD 850W**

**MPX-8503-AFAG-2\*\*\***

## BUILT TO LAST



## FEATURES

**80 PLUS Gold Certified :** The GX II Gold is certified to achieve more than 90% efficiency at typical loads.

**Fully support ATX3.0 :** ATX 3.0 compatibility and a 12VHPWR connector enable peak power support up to 200% more than the unit's rated power.

**Smart Thermal Control Mode :** A zero-RPM default mode automatically turns the fan on when your PC reaches a specific temperature.

**Fully Modular Cable Management :** Efficiently reduces clutter, increases airflow, and improves overall efficiency and thermal performance.

**10 Year Warranty :** This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.

## PACKAGE INFORMATION

Cable Type	EAN	UPC
MPX-8503-AFAG-2BUS	4719512140215	884102112539
MPX-8503-AFAG-2BUK	4719512140222	884102112546
MPX-8503-AFAG-2BEU	4719512140239	884102112553
MPX-8503-AFAG-2BST	4719512140246	884102112560
MPX-8503-AFAG-2BAU	4719512140253	884102112577
MPX-8503-AFAG-2BBR	4719512140260	884102112584
MPX-8503-AFAG-2BKR	4719512140277	884102112591
MPX-8503-AFAG-2BTW	4719512140284	884102112607
MPX-8503-AFAG-2BJP	4719512140291	884102112614
MPX-8503-AFAG-2BIN	4719512140307	884102112621
MPX-8503-AFAG-2BWO	4719512140314	884102112638

Nett Weight	2.614 kg / 5.762 lb
Gross Weight	3.004 kg / 6.622 lb
Package Dimensions	320 x 195 x 125mm (12.59 x 7.68 x 4.92")
Carton Dimensions	520 x 335 x 231mm (20.47 x 13.18 x 9.09")
Unit / Carton	4 pcs
Carton / Pallet	24 pcs

The GX II Gold brings a new standard of durability and efficiency to Cooler Master's lineup of power supply units. Its APFC half-bridge +LLC, and DC-to-DC has achieved an 80 Plus Gold efficiency certification while maintaining top-tier performance. A smart thermal control mode and zero-RPM default mode effectively reduce noise and improve heat dissipation simultaneously. Combined with an ATX 3.0 12VHPWR native cable featuring a space-saving 90-degree connector, the GX II Gold is a full-featured powerhouse.

## SPECIFICATIONS


Product Name	GXII Gold 850W	
Item Code	MPX-8503-AFAG-2***	
ATX Version	ATX 12V Ver. 3.0	
PFC	Active PFC	
Input Voltage	100-240V	
Input Current	10 - 5A	
Input Frequency	50 - 60Hz	
Dimensions (L x W x H)	160 x 150 x 86mm	
Fan Size	120mm	
Fan Bearing	HDB	
Fan Speed	2500±10% rpm	
Efficiency	≥ 90% @ Typical Load	
80 PLUS Rating	80 PLUS Gold	
ErP 2014 Lot 3	Yes	
Operating Temperature	0 ~ 40°C	
Power Good Signal	100-150 ms	
Hold Up Time	≥ 16ms @80%Load	
MTBF	>100,000 hours	
Protections	OPP/ OVP/ OTP/ OCP/ SCP/ UVP/ Surge & Inrush Protection	
Regulatory	cTUVus, TUV, CE, FCC, BSMI, CCC, EAC, RCM, UKCA, RoHS2.0 / BIS, KC (based on region's request.)	
Connectors	ATX 24 Pin	x1 = 1x (550mm)
	EPS 4+4 Pin	x1 = 1x (600mm)
	EPS 8 Pin	x1 = 1x (600mm)
	SATA	x6 = 2x (500(s)+120(s)+120(s)+120(p)mm)
	Peripheral 4 Pin	x2 = 2x (500(s)+120(s)+120(s)+120(p)mm)
	PCI-e 6+2 Pin	x4 = 2x (500+120mm)
	12VHPWR	x1 = 1x (650mm)

AC INPUT	100-240V~ 10 - 5A 50 - 60Hz				
DC OUTPUT	+3.3V	+5V	+12V	-12V	+5Vstb
	20A	20A	70.8A	0.3A	3A
TOTAL POWER	120W		849.6W	3.6W	15W
	850W				



Make It Yours.

## FEATURES



12VHPWR native cable with 90 degree connector provides easy installation.



The GX II Gold is certified to achieve more than 90% efficiency at typical loads.



Fully Modular cabling improves consumer cable management.



High-quality Japanese bulk capacitors have been used to improve reliability.



ATX 3.0 compatibility and a 12VHPWR connector enable peak power support up to 200% more than the unit's rated power.



This unit comes with a standard limited manufacturing warranty of 10 years from the date of purchase.

